

1008007000

IPDDS

IP Dual Display Station



- ✓ Compatible with AlphaCom, IC-EDGE and iPBXs (SIP)
- ✓ Remote software upgrade, configuration and monitoring
- ✓ Powered from the IP network cable using Power over Ethernet (PoE)
- ✓ Superb audio quality – high bandwidth codec, active noise cancellation, acous and high output power amplifier
- ✓ Displays with backlight
- ✓ The station may use up to 90 Direct Access Keys (DAK) on 9 dynamic DAK pad have letters to be used for search
- ✓ facility in the intercom directory and display text editing
- ✓ The station has 4 dynamic navigation keys for quick access to system menus :
- ✓ Status information, guidance and menus are shown on a large 4 line graphic d

Description

The IP Dual Display Station is designed for table-top mounting in bank/finance and office environments. It is also well suited as a control room station. The physical size makes it easy to place on desks with limited space. An optional noise cancelling gooseneck microphone module can be mounted in noisy environments. The two backlit easy-to-read displays and navigation buttons provide single-touch access to stations, group calls, audio monitoring, public address zones, radio channels, the opening of doors and gates as well as other functions. The direct access keys are easily programmed from the station and can be changed at any time. The display may be edited to show your personal text.

The station connects directly to the IP network, making it easy to deploy anywhere at any distance. The built-in web server allows monitoring, configuration and software updates over the IP network; making it the easiest way to maintain a remotely located station.

Designed for CCoIP®, the station offers a set of critical communication features such as group call, call priority and override of the speaker volume. This enables the delivery of instant, efficient and secure voice and data services in an IP environment.

Like all Vingtor-Stentofon stations, this IP desktop station features superb audio quality. This is enabled through a set of advanced technologies such as active noise filtering, acoustic echo cancellation, wide band audio codec, and high power audio outputs.




The IP station has an integrated managed data switch providing advanced networking and security features. The integrated switch provides support for:

- ✓ Protection from unwanted access
- ✓ Quality of Service (QoS) by managing data traffic
- ✓ Increased system availability through redundant LAN infrastructure
- ✓ Cost efficient installation by providing shared network connections

To provide maximum availability the station comes with advanced supervision functions. The station line test will detect if there is any faults in the network or station electronics. In addition the station supports tone test, testing the complete transmission path including microphone and speaker. The status of the stations is reported to AlphaWeb as well as to 3rd party management systems using SNMP, Syslog or OPC.

See also: [additional documentation on wiki.zenitel.com](http://wiki.zenitel.com)

Technical Dimensions



Specifications

MECHANICAL

Order Number	1008007000
Mounting	Table top
Dimensions: (W x H x D)	72 x 140 x 270 mm, 2.8 x 5.5 x 10.6 inch
Weight	0.4 kg
Temperature range	0°C - 55°C, 32°C - 131°F
Humidity	Non condensing, 10% - 85% RH
Max SPL	85 dB at 1m
Loudspeaker Impedance	8 ohm
Frequency Range	300 - 7000 Hz
Connector	1 x RJ45 (Ethernet) 10/100 Mbps
Direct access display	10 lines, 5-8 characters graphic
Information display	4 lines, 20 characters graphic
Power consumption	Power over Ethernet, IEEE 802.3 a-f, Class 0, Idle 4W, max. 8W
IP protocols	IP v4 - TCP - UDP - HTTPS – TFTP - RTP - RTCP -DHCP - SNMP - DiffServ - TOS – STENTOFONCCoIP®
LAN protocols	Power over Ethernet (IEEE 802.3 a-f), VLAN(IEEE 802.1pq), Network Access Control (IEEE 802.1x)
Audio technology	Wideband 200 Hz - 7 kHz (G.722), Telephony 3.4kHz (G.711), Active noise filtering, Acoustic echo cancellation, Open duplex, Adaptive jitter filter, Handset and volume override
Management and operation	HTTPS (Web configuration), DHCP and static IP, Remote automatic software upgrade, Centralized monitoring, Status LED

Accessories



MDDS

Microphone for Dual Display Station

deining
elektronik gmbh & co. kg

Rudolf-Diesel-Str. 4 • 76356 Weingarten
Tel. +49 (7244) 7016-0 • Fax +49 (7244) 7016-33

info@deining-gmbh.de • www.deining-gmbh.de